



Bamboo Flooring



Innovations in Bamboo



Edge Grain Amber



Edge Grain Natural



Flat Grain Amber



Flat Grain Natural

Material

100% Bamboo

Standard Sizes

5/8" x 3 3/4" x 75"
1/2" x 3" x 72"

Finish

Multi-coat Aluminum Oxide System

Fire Rating

0.45 meets class I rating
ASTM E-648 critical radiant flux

Emissions

0.045 hcho (mg/L)
0.30 meets US HUD standard,
0.045 registers a near zero output
(NVLAP 23/T02 and FTM I-1983)

Hardness Rating

Average Hardness 1700 psi
Janka Ball Hardness Test (ASTM D1037)

Relative Stability

parallel 0.06
thickness 0.4
(ASTM D1037)

Finish Rating

23,500 rotations, 4B adhesion rating
(ASTM D4060, CS 17 wheel, taber abrasion
ASTM D3359 adhesion)

Slip Resistance

Static Friction coefficient 0.522
Sliding Friction coefficient 0.564
(ASTM D2394)

Unique to the hardwood flooring industry, Plyboo® bamboo flooring has grown in popularity and can now be found in homes all over America. With its easy installation, durability, and good looks, homeowners are choosing Plyboo® for its adaptability to design themes, from contemporary to tropical, from traditional to that Asian touch.

toll-free 866.835.9859

www.plyboo.com

LEED™ Certification

Plyboo® flooring is manufactured from 100% bamboo, a rapidly renewable material and a contributing finish under the 6.0 Section of the U.S. Green Building Council's LEED™ Materials and Resource Point System.